

IP65
WATERPROOF

PORTABLE CONDUCTIVITY/TDS METER
PART NO. 0411-0200



- Reading mode: auto-read and continuous-read
- Automatic/manual temperature compensation
- Auto-hold feature senses and locks the measurement endpoint
- Cell constant is settable
- 1 point calibration with standard recognition
- Data capacity up to 200 sets for each parameter
- IP65 dust/waterproof
- Auto power off



wristband (included)



standard solution (included)

SPECIFICATION

| | | |
|---------------------|---|--|
| Conductivity | Range | 0.00 μ S/cm~200mS/cm |
| | Resolution | 0.01 μ S/cm minimum |
| | Electronic unit accuracy | \pm 1.0%FS |
| | Measurement accuracy | \pm 1.5%FS |
| | Reference temperature | 77°F/25°C |
| | Calibration point | 1 |
| | Standard recognition | 84 μ S/cm, 1413 μ S/cm, 12.88mS/cm |
| TDS | Range | 0.00mg/L~300g/L |
| | Resolution | 0.01mg/L minimum |
| | Accuracy | \pm 1.0%FS |
| Temperature | Range | 23~230°F/-5~110°C |
| | Resolution | .2°F/.1°C |
| | Accuracy | \pm .7°F/ \pm .4°C |
| Input | electrode with 5-pin aviation connector | |
| Power supply | rechargeable battery | |
| Dimension | 3.1×8.9×1.4" | |
| Weight | .88lb | |

STANDARD DELIVERY

| | |
|---|----------|
| Main unit | 1 pc |
| Electrode | 1 pc |
| Electrode holder | 2 pcs |
| Wristband | 1 pc |
| Silicone rubber case | 1 pc |
| AC/DC adapter and charging cable | 1 pc |
| Standard solution | 1 bottle |