

VIBRATION ISOLATION PLATFORMS (BASIC TYPE)

CUSTOMIZABLE

- Suitable for equipment with low vibration requirement
- Stable and reliable in structure, convenient to install, and requiring little post-maintenance
- Effectively reduce the vibration energy in medium-high frequency ranges, and effectively isolate external vibration disturbances
- Vibration isolation support adopts rubber vibration damper


0790-B129B

STANDARD DELIVERY

Main unit	1 pc
Rubber vibration damper	4 pcs

SPECIFICATION

Part No.	0790-B88A	0790-B88B	0790-B108A	0790-B108B	0790-B129A	0790-B129B
Countertop material	marble	honeycomb platen	marble	honeycomb platen	marble	honeycomb platen
Threaded hole/pitch	—	M6/.98×.98"	—	M6/.98×.98"	—	M6/.98×.98"
Countertop thickness	3.94"		3.94"		3.94"	
Max. load	881.8lb		881.8lb		1322.7lb	
Foot	foot cup+caster		foot cup+caster		foot cup+caster	
Dimension (L×W×H)	31.5×31.5×31.5"		39.4×31.5×31.5"		47.2×35.4×31.5"	
Weight	573.2lb	352.7lb	727.5lb	507.1lb	771.6lb	551.2lb

SPECIFICATION

Part No.	0790-B159A	0790-B159B	0790-B1812A	0790-B1812B	0790-B2012A	0790-B2012B
Countertop material	marble	honeycomb platen	marble	honeycomb platen	marble	honeycomb platen
Threaded hole/pitch	—	M6/.98×.98"	—	M6/.98×.98"	—	M6/.98×.98"
Countertop thickness	7.87"		7.87"		7.87"	
Max. load	1322.8lb		1763.7lb		1763.7lb	
Foot	foot cup+caster		foot cup+caster		foot cup+caster	
Dimension (L×W×H)	59.1×35.4×31.5"		70.9×47.2×31.5"		78.7×47.2×31.5"	
Weight	1653.5lb	1322.8lb	1763.7lb	1433.0lb	1873.9lb	1543.2lb

Natural frequency	vertical: 5Hz~10Hz horizontal: 4Hz~8Hz	
Vibration isolation mode	rubber vibration damper	
Leveling mode	manual leveling	
Height adjustment	±.78"	
Platform height	31.5"	
Countertop flatness	marble: grade AA (GGG-P-463C) honeycomb platen: 0.05mm/m ² ~0.1mm/m ²	