


# DIGITAL INSIDE GROOVE CALIPERS

depth stop **6143**  
(optional)



preset buttons





**1120-150AE**  
type A

- Measure groove diameter
- Resolution: .0005"/0.01mm
- Buttons type A: on/off, set, inch/mm, preset (+, -)  
type B: on/off, zero, inch/mm  
type C: on/off, zero, inch/mm, ABS/REL, hold
- Battery CR2032
- Made of stainless steel
- Optional accessory: depth stop  
(part no. **6143**, for calipers with c=.630")



**1120-150B**  
type B



**1120-150P**  
type C

**No dust/waterproof, preset (no need to add the width of the jaws on the reading), with data interface**

Part No.	Range	Type	Accuracy	L	a	b	c	d	e	Data output cable (optional)
<b>1120-150AE</b>	1-6"/25.4-150mm	A	±.0015"	9.843"	.197"	.500"	.630"	1.181"	.039"	<b>7315-21, 7302-21</b>
<b>1120-1501</b>	1.38-6"/35-150mm	A	±.0025"	9.843"	.236"	.689"	.630"	2.362"	.059"	<b>7315-21, 7302-21</b>
<b>1120-200A</b>	.98-8"/25-200mm	A	±.0015"	12.205"	.197"	.492"	.630"	1.575"	.039"	<b>7315-21, 7302-21</b>
<b>1120-2001</b>	1.57-8"/40-200mm	A	±.0025"	12.205"	.276"	.787"	.630"	2.756"	.098"	<b>7315-21, 7302-21</b>
<b>1120-300A</b>	1.18-12"/30-300mm	A	±.0020"	16.142"	.197"	.591"	.630"	1.969"	.059"	<b>7315-21, 7302-21</b>
<b>1120-3001</b>	1.97-12"/50-300mm	A	±.0030"	16.142"	.315"	.984"	.630"	3.150"	.098"	<b>7315-21, 7302-21</b>
<b>1120-500</b>	1.57-20"/40-500mm	A	±.0030"	26.772"	.197"	.787"	.945"	3.543"	.087"	<b>7315-22, 7302-22</b>
<b>1120-5001</b>	2.36-20"/60-500mm	A	±.0030"	26.772"	.394"	1.181"	.945"	4.724"	.134"	<b>7315-22, 7302-22</b>
<b>1120-5002</b>	3.15-20"/80-500mm	A	±.0030"	26.772"	.630"	1.575"	.945"	5.906"	.205"	<b>7315-22, 7302-22</b>

**No dust/waterproof, preset (no need to add the width of the jaws on the reading), built-in wireless (receiver part no. 7315-2/3/6/7/8 is required)**

Part No.	Range	Type	Accuracy	L	a	b	c	d	e
<b>1120-150AEWL</b>	1-6"/25.4-150mm	A	±.0015"	9.843"	.197"	.500"	.630"	1.181"	.039"
<b>1120-1501WL</b>	1.38-6"/35-150mm	A	±.0025"	9.843"	.236"	.689"	.630"	2.362"	.059"
<b>1120-200AWL</b>	.98-8"/25-200mm	A	±.0015"	12.205"	.197"	.492"	.630"	1.575"	.039"
<b>1120-2001WL</b>	1.57-8"/40-200mm	A	±.0025"	12.205"	.276"	.787"	.630"	2.756"	.098"
<b>1120-300AWL</b>	1.18-12"/30-300mm	A	±.0020"	16.142"	.197"	.591"	.630"	1.969"	.059"
<b>1120-3001WL</b>	1.97-12"/50-300mm	A	±.0030"	16.142"	.315"	.984"	.630"	3.150"	.098"
<b>1120-500WL</b>	1.57-20"/40-500mm	A	±.0030"	26.772"	.197"	.787"	.945"	3.543"	.087"
<b>1120-5001WL</b>	2.36-20"/60-500mm	A	±.0030"	26.772"	.394"	1.181"	.945"	4.724"	.134"
<b>1120-5002WL</b>	3.15-20"/80-500mm	A	±.0030"	26.772"	.630"	1.575"	.945"	5.906"	.205"

**No dust/waterproof, no preset (need to add the width of the jaws on the reading)**

Part No.	Range	Type	Accuracy	L	a	b	c	d	e
<b>1120-150B</b>	1.97-6"/50-150mm	B	±.0025"	10.630"	.315"	.984"	.787"	3.543"	.134"
<b>1120-200B</b>	2.36-8"/60-200mm	B	±.0025"	12.598"	.394"	1.181"	.787"	3.937"	.134"
<b>1120-300B</b>	2.36-12"/60-300mm	B	±.0030"	16.535"	.394"	1.181"	.787"	4.331"	.134"

**IP67 dust/waterproof, no automatic power off, set zero after power on each time, no preset (need to add the width of the jaws on the reading), without data interface**

Part No.	Range	Type	Accuracy	L	a	b	c	d	e
<b>1120-150P</b>	.87-6"/22-150mm	C	±.0015"	9.843"	.197"	.433"	.630"	1.181"	.039"