


## DIGITAL DEPTH GAGES (STANDARD TYPE)

- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Meet DIN862 (except 0-20"/0-500mm, 0-40"/0-1000mm, 0-60"/0-1500mm)
- Battery CR2032
- Made of stainless steel



1141-150A



### With data interface

Part No.	Range	Resolution	Accuracy	L	a	b	d	Data output cable (optional)
1141-150A	0-6"/0-150mm	.0005"/0.01mm	±.0015"	9.055"	.236"	.571"	3.937"	7315-21, 7302-21
1141-200A	0-8"/0-200mm	.0005"/0.01mm	±.0015"	11.024"	.236"	.571"	3.937"	7315-21, 7302-21
1141-300A	0-12"/0-300mm	.0005"/0.01mm	±.0015"	14.961"	.236"	.571"	5.906"	7315-21, 7302-21
1141-500A	0-20"/0-500mm	.0005"/0.01mm	±.0020"	23.031"	.276"	.591"	5.906"	7315-22, 7302-22
1141-5001A	0-20"/0-500mm	.0005"/0.01mm	±.0020"	23.031"	.276"	.591"	7.874"	7315-22, 7302-22
1141-1000A	0-1000mm/0-40"	.0005"/0.01mm	±.0028"	46.772"	.276"	.709"	5.906"	7315-22, 7302-22
1141-10001A	0-1000mm/0-40"	.0005"/0.01mm	±.0028"	46.772"	.276"	.709"	7.874"	7315-22, 7302-22
1141-10002A	0-1000mm/0-40"	.0005"/0.01mm	±.0028"	46.772"	.276"	.709"	9.843"	7315-22, 7302-22
1141-10003A	0-1000mm/0-40"	.0005"/0.01mm	±.0028"	46.772"	.276"	.709"	11.811"	7315-22, 7302-22
1141-1500A	0-1500mm/0-60"	.0005"/0.01mm	±.0043"	66.732"	.276"	.709"	7.874"	7315-22, 7302-22

### Built-in wireless(receiver code 7315-2/3/6/7/8 is required)

Part No.	Range	Resolution	Accuracy	L	a	b	d
1141-150AWL	0-6"/0-150mm	.0005"/0.01mm	±.0015"	9.055"	.236"	.571"	3.937"
1141-200AWL	0-8"/0-200mm	.0005"/0.01mm	±.0015"	11.024"	.236"	.571"	3.937"
1141-300AWL	0-12"/0-300mm	.0005"/0.01mm	±.0015"	14.961"	.236"	.571"	5.906"
1141-500AWL	0-20"/0-500mm	.0005"/0.01mm	±.0020"	23.031"	.276"	.591"	5.906"
1141-5001AWL	0-20"/0-500mm	.0005"/0.01mm	±.0020"	23.031"	.276"	.591"	7.874"