





DIGITAL HOOK DEPTH GAGES

DATA
OUTPUT



1142-150A

- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel



With data interface

Part No.	Range	Accuracy	L	d	a	b	c	Data output cable (optional)
1142-150A	0-6"/0-150mm	±.0015"	9.055"	3.937"	.197"	.079"	.571"	7315-21, 7302-21
1142-200A	0-8"/0-200mm	±.0015"	11.024"	3.937"	.197"	.079"	.571"	7315-21, 7302-21
1142-300A	0-12"/0-300mm	±.0015"	14.961"	5.906"	.197"	.079"	.571"	7315-21, 7302-21
1142-500A	0-20"/0-500mm	±.0020"	23.031"	5.906"	.315"	.118"	.591"	7315-22, 7302-22
1142-5001A	0-20"/0-500mm	±.0020"	23.031"	7.874"	.315"	.118"	.591"	7315-22, 7302-22
1142-1000A	0-40"/0-1000mm	±.0030"	46.772"	5.906"	.394"	.157"	.709"	7315-22, 7302-22
1142-10001A	0-40"/0-1000mm	±.0030"	46.772"	7.874"	.394"	.157"	.709"	7315-22, 7302-22
1142-10002A	0-40"/0-1000mm	±.0030"	46.772"	9.843"	.394"	.157"	.709"	7315-22, 7302-22

Built-in wireless(receiver code 7315-2/3/6/7/8 is required)

Part No.	Range	Accuracy	L	d	a	b	c
1142-150AWL	0-6"/0-150mm	±.0015"	9.055"	3.937"	.197"	.079"	.571"
1142-200AWL	0-8"/0-200mm	±.0015"	11.024"	3.937"	.197"	.079"	.571"
1142-300AWL	0-12"/0-300mm	±.0015"	14.961"	5.906"	.197"	.079"	.571"
1142-500AWL	0-20"/0-500mm	±.0020"	23.031"	5.906"	.315"	.118"	.591"
1142-5001AWL	0-20"/0-500mm	±.0020"	23.031"	7.874"	.315"	.118"	.591"