


DIGITAL DOUBLE HOOK DEPTH GAGES

DATA
OUTPUT

- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Meet DIN862
- Battery CR2032
- Made of stainless steel



1144-150A



With data interface

Part No.	Range	Accuracy	L	d	a	b	c	e	Data output cable (optional)
1144-150A	0-6"/0-150mm	±.0015"	9.173"	3.937"	.846"	.138"	.571"	.098"	7315-21, 7302-21
1144-200A	0-8"/0-200mm	±.0015"	11.142"	3.937"	.846"	.138"	.571"	.098"	7315-21, 7302-21
1144-300A	0-12"/0-300mm	±.0015"	15.079"	5.906"	.846"	.138"	.571"	.098"	7315-21, 7302-21
1144-500A	0-20"/0-500mm	±.0020"	23.031"	5.906"	.984"	.197"	.571"	.118"	7315-22, 7302-22
1144-5001A	0-20"/0-500mm	±.0020"	23.031"	7.874"	.984"	.197"	.591"	.118"	7315-22, 7302-22
1144-1000A	0-40"/0-1000mm	±.0030"	46.772"	5.906"	1.260"	.276"	.709"	.157"	7315-22, 7302-22
1144-10001A	0-40"/0-1000mm	±.0030"	46.772"	7.874"	1.260"	.276"	.709"	.157"	7315-22, 7302-22
1144-10002A	0-40"/0-1000mm	±.0030"	46.772"	9.843"	1.260"	.276"	.709"	.157"	7315-22, 7302-22

Built-in wireless(receiver code 7315-2/3/6/7/8 is required)

Part No.	Range	Accuracy	L	d	a	b	c	e
1144-150AWL	0-6"/0-150mm	±.0015"	9.173"	3.937"	.846"	.138"	.571"	.098"
1144-200AWL	0-8"/0-200mm	±.0015"	11.142"	3.937"	.846"	.138"	.571"	.098"
1144-300AWL	0-12"/0-300mm	±.0015"	15.079"	5.906"	.846"	.138"	.571"	.098"
1144-500AWL	0-20"/0-500mm	±.0020"	23.031"	5.906"	.984"	.197"	.571"	.118"
1144-5001AWL	0-20"/0-500mm	±.0020"	23.031"	7.874"	.984"	.197"	.591"	.118"

