




1186-150A

- The left jaw can slide up and down to facilitate measurement of stepped sections
- Resolution: .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel



With data interface (data output cable part no. 7315-21, 7302-21, optional)

Part No.	Range	Accuracy	L	a	b	c	d	e	f
1186-150A	0-6"/0-150mm	±.0015"	9.803"	1.575"	.650"	.394"	4.331"	.669"	.276"
1186-200A	0-8"/0-200mm	±.0015"	11.772"	1.969"	.768"	.394"	4.724"	.669"	.276"
1186-300A	0-12"/0-300mm	±.0020"	15.709"	2.362"	.807"	.394"	5.118"	.669"	.276"

Built-in wireless (receiver part no. 7315-2/3/6/7/8/9 is required)

Part No.	Range	Accuracy	L	a	b	c	d	e	f
1186-150AWL	0-6"/0-150mm	±.0015"	9.803"	1.575"	.650"	.394"	4.331"	.669"	.276"
1186-200AWL	0-8"/0-200mm	±.0015"	11.772"	1.969"	.768"	.394"	4.724"	.669"	.276"
1186-300AWL	0-12"/0-300mm	±.0020"	15.709"	2.362"	.807"	.394"	5.118"	.669"	.276"

