


ADJUSTABLE SNAP GAGES

FAST AND ACCURATE
MEASUREMENT FOR CYLINDERS

| Part No. | Range | L | A | B | E | F | H | d (DIA) |
|----------|--------------|---------|-------|--------|-------|--------|---------|---------|
| 2187-6 | 0-.24" | 2.913" | .591" | .689" | .480" | 1.071" | 2.815" | .276" |
| 2187-13 | .24-.51" | 3.346" | .591" | 1.024" | .480" | 1.071" | 3.130" | .484" |
| 2187-19 | .51-.75" | 3.661" | .591" | 1.063" | .480" | 1.071" | 3.268" | .484" |
| 2187-25 | .75-.98" | 3.937" | .591" | 1.319" | .480" | 1.071" | 3.524" | .484" |
| 2187-32 | .98-1.26" | 4.370" | .709" | 1.516" | .598" | 1.386" | 4.094" | .602" |
| 2187-38 | 1.26-1.50" | 4.606" | .709" | 1.634" | .598" | 1.386" | 4.134" | .602" |
| 2187-44 | 1.50-1.73" | 4.843" | .709" | 1.752" | .598" | 1.386" | 4.291" | .602" |
| 2187-51 | 1.73-2.01" | 5.118" | .709" | 1.890" | .598" | 1.386" | 4.606" | .602" |
| 2187-57 | 2.01-2.24" | 5.354" | .709" | 1.772" | .598" | 1.386" | 4.685" | .602" |
| 2187-63 | 2.24-2.48" | 5.630" | .709" | 1.969" | .598" | 1.386" | 4.803" | .602" |
| 2187-70 | 2.48-2.76" | 6.142" | .787" | 2.283" | .598" | 1.386" | 5.197" | .602" |
| 2187-76 | 2.76-2.99" | 6.417" | .787" | 2.382" | .598" | 1.386" | 5.394" | .602" |
| 2187-82 | 2.99-3.23" | 6.654" | .787" | 2.539" | .598" | 1.386" | 5.512" | .602" |
| 2187-89 | 3.23-3.50" | 6.890" | .787" | 2.618" | .598" | 1.386" | 5.748" | .602" |
| 2187-95 | 3.50-3.74" | 7.126" | .787" | 2.736" | .598" | 1.386" | 5.866" | .602" |
| 2187-101 | 3.74-3.98" | 7.402" | .787" | 2.756" | .598" | 1.386" | 6.063" | .602" |
| 2187-108 | 3.98-4.25" | 7.795" | .945" | 3.110" | .598" | 1.543" | 6.535" | .602" |
| 2187-114 | 4.25-4.49" | 8.031" | .945" | 3.189" | .598" | 1.543" | 6.772" | .602" |
| 2187-120 | 4.49-4.72" | 8.268" | .945" | 3.386" | .598" | 1.543" | 7.047" | .602" |
| 2187-127 | 4.72-5.00" | 8.543" | .945" | 3.524" | .598" | 1.543" | 7.323" | .602" |
| 2187-133 | 5.00-5.24" | 8.780" | .945" | 3.642" | .598" | 1.543" | 7.559" | .602" |
| 2187-139 | 5.24-5.47" | 9.016" | .945" | 3.760" | .598" | 1.543" | 7.756" | .602" |
| 2187-146 | 5.47-5.75" | 9.252" | .945" | 3.878" | .598" | 1.543" | 7.913" | .602" |
| 2187-152 | 5.75-5.98" | 9.528" | .945" | 4.016" | .598" | 1.543" | 8.071" | .602" |
| 2187-163 | 5.98-6.42" | 10.748" | .843" | 4.201" | .717" | 1.543" | 8.307" | .720" |
| 2187-175 | 6.42-6.89" | 10.748" | .843" | 4.201" | .717" | 1.543" | 8.307" | .720" |
| 2187-188 | 6.89-7.40" | 11.752" | .843" | 4.713" | .717" | 1.543" | 8.937" | .720" |
| 2187-200 | 7.40-7.87" | 11.752" | .843" | 4.713" | .717" | 1.543" | 8.937" | .720" |
| 2187-213 | 7.87-8.39" | 12.756" | .843" | 5.185" | .717" | 1.543" | 9.528" | .720" |
| 2187-225 | 8.39-8.86" | 12.756" | .843" | 5.185" | .717" | 1.543" | 9.528" | .720" |
| 2187-238 | 8.86-9.37" | 13.760" | .843" | 5.697" | .717" | 1.543" | 9.843" | .720" |
| 2187-250 | 9.37-9.84" | 13.760" | .843" | 5.866" | .717" | 1.543" | 9.843" | .720" |
| 2187-263 | 9.84-10.35" | 14.783" | .843" | 6.209" | .717" | 1.543" | 10.945" | .720" |
| 2187-275 | 10.35-10.83" | 14.783" | .843" | 6.209" | .717" | 1.543" | 10.945" | .720" |
| 2187-288 | 10.83-11.34" | 15.748" | .843" | 6.720" | .717" | 1.543" | 11.457" | .720" |
| 2187-300 | 11.34-11.81" | 15.748" | .843" | 6.720" | .717" | 1.543" | 11.457" | .720" |




2187-6



0-.24"



2187-19



over .24"

- Used as Go/No-Go gage by setting upper and lower limits
- Flatness of anvil: 59µin
- Parallelism of measuring faces:
range 0-1.26": 118µin
range 1.26-3.50": 157µin
range 3.50-11.81": 197µin