## **BORE GAGE SETS**

ATTENTION: NOT SUITABLE FOR .00005", .0001" OR 0.001MM DIAL INDICATORS









with digital indicator

read the diameter directly, after imputing the size of setting ring.



the minimum value tracking function can find the diameter automatically.

with waterproof digital indicator

2724-S3EWP

read the diameter directly, after imputing the size of setting ring.



the minimum value tracking function can find the diameter automatically.



 Optional accessory: setting ring (part no. 6313), long handle (part no. 7351), bore gage setter

## With dial indicator

TTICH GIGH HI	a.oato.				
Part No.	Range	Indicator	Bore gages included	Accuracy	Repeatability
2824-S2E	1.4-6"	dial indicator, range .25", graduation .0005"	① 1.4-2" (dial indicator and handle are not included) ② 2-6"	1.4-2" ±.0009" 2-6" ±.0009"	.00015"
2824-S3E	.7-6"	dial indicator, range .25", graduation .0005"	① .7-1.5" ② 1.4-2.4" (dial indicator is not included) ③ 2-6" (dial indicator is not included)	.7-1.5" ±.00075" 1.4-2.4" ±.0009" 2-6" ±.0009"	.00015"

## With digital indicator (data output cable part no. 7315-50M page 5, 7302-40M page 13, optional)

Part No.	Range	Indicator	Bore gages included	Accuracy	Repeatability
2724-S2E	1.4-6"	digital indicator, part no. <b>2108-10EF</b> , range .5"/12.7mm, resolution .0001"/0.002mm (can switch to .0005"/0.01mm)	① 1.4-2" (digital indicator and handle are not included) ② 2-6"	1.4-2" ±.0009" 2-6" ±.0009"	.0001"
2724-S3E	.7-6"	digital indicator, part no. <b>2108-10EF</b> , range .5"/12.7mm, resolution .0001"/0.002mm (can switch to .0005"/0.01mm)	① .7-1.5" ② 1.4-2.4" (digital indicator is not included) ③ 2-6" (digital indicator is not included)	.7-1.5" ±.00075" 1.4-2.4" ±.0009" 2-6" ±.0009"	.0001"

With digital indicator (data output cable part no. 7315-50M page 5, 7302-40M page 13, optional)

Part No. Range Indicator Bore gages included

waterproof digital indicator

resolution .0001"/0.002mm (can switch to .0005"/0.01mm)

2724-S2EWP	1.4-6"	part no. 2137-10EF, range .5"/12.7mm, dust/waterproof IP54, resolution .0001"/0.002mm (can switch to .0005"/0.01mm)	① 1.4-2" (digital indicator and handle are not included) ② 2-6"	1.4-2" 2-6"	±.0009" ±.0009"	.0001"
2724-S3EWP	.7-6"	waterproof digital indicator, part no. <b>2137-10EF</b> , range .5"/12.7mm, dust/waterproof IP54,	① .7-1.5" ② 1.4-2.4" (digital indicator is not included)	.7-1.5" 1.4-2.4"	±.00075" ±.0009"	.0001"

3 2-6" (digital indicator is not included)

Repeatability

Accuracy

2-6"

+.0009"