

DIGITAL TUBULAR INSIDE MICROMETERS WITH INTERCHANGEABLE POINTS








■ IP65 dust/waterproof ■ Resolution: .00005"/0.001mm Accuracy: [.00005(3+n+L/2)]"

n=number of rods L=maximum measuring length (inch)

- Button function: on/off, set, inch/mm, data transmission
- Data output
- Automatic power off
- Power:

with data interface: CR2032 built-in wireless: rechargeable lithium battery

■ Optional accessory: gauge blocks (part no. 4112-B8). gauge block holder (6886 series), gauge block accessory (part no. 6881-C)



are optional

With data interface (optional wireless transmitter part no. 7315-31, receiver is needed page 8)

| Part No. | Range * | Travel of micrometer head | Extension rods |
|----------|----------|---------------------------|---|
| 3525-9 | 8-8.85" | .85" | _ |
| 3525-42 | 8-41.85" | .85" | 1", 2" (2 pcs), 4", 8", 16" |
| 3525-62 | 8-61.85" | .85" | 1", 2" (2 pcs), 4" (2 pcs), 8", 16" (2 pcs) |
| 3525-82 | 8-81.85" | .85" | 1", 2" (2 pcs), 4", 8" (2 pcs), 16" (3 pcs) |

^{*}Range after installing ball points

Built-in wireless (receiver part no. 7315-2/3/6/7/8/9 is needed)

| Part No. | |
|------------|--|
| 3525-000WL | |


Part no. examples:

| Original part no. | Wireless part no. |
|-------------------|-------------------|
| 3525-9 | 3525-9WL |
| 3525-42 | 3525-42WL |

Ball points (optional)**

- Supplied in pair
- Made of carbide

| Part No. | D |
|-------------------|-------------------|
| 3525-1H4 | 1/4" D I A |
| 3525-3H8 | 3/8" D I A |
| 3525 - 1H2 | 1/2" D I A |
| 3525-5H8 | 5/8" D I A |



^{**}Points can be customized according to customers' requirements