

WHITWORTH PIPE THREAD RING GAGE(G SERIES)

- Standard ISO 228
- Material: OHNS
(Oil Hardened Non-shrinking Steel),
- Stable dimension and wear resistance
- Hardness HRC60-62
- Supplied with manufacturer inspection certificate
(except G 4-11 and above)



4635-1A14



4635-1A14N

Size	Part No. (4635)			
	Class A		Class B	
	GO	NOGO	GO	NOGO
G 1/16 - 28	4635-1D28	4635-1D28N	—	—
G 1/8 - 28	4635-1C28	4635-1C28N	4635-1C28B	4635-1C28BN
G 1/4 - 19	4635-1B19	4635-1B19N	4635-1B19B	4635-1B19BN
G 3/8 - 19	4635-3C19	4635-3C19N	4635-3C19B	4635-3C19BN
G 1/2 - 14	4635-1A14	4635-1A14N	4635-1A14B	4635-1A14BN
G 5/8 - 14	4635-5C14	4635-5C14N	—	—
G 3/4 - 14	4635-3B14	4635-3B14N	4635-3B14B	4635-3B14BN
G 7/8 - 14	4635-7C14	4635-7C14N	—	—
G 1 - 11	4635-111	4635-111N	4635-111B	4635-111BN
G 1 1/8 - 11	4635-1F11	4635-1F11N	—	—
G 1 1/4 - 11	4635-1G11	4635-1G11N	—	—
G 1 1/2 - 11	4635-1H11	4635-1H11N	4635-1H11B	4635-1H11BN

Size	Part No. (4635)	
	Class A	
	GO	NOGO
G 1 3/4 - 11	4635-3G11	4635-3G11N
G 2 - 11	4635-211	4635-211N
G 2 1/4 - 11	4635-1K11	4635-1K11N
G 2 1/2 - 11	4635-1J11	4635-1J11N
G 2 3/4 - 11	4635-3K11	4635-3K11N
G 3 - 11	4635-311	4635-311N
G 3 1/2 - 11	4635-1N11	4635-1N11N
G 4 - 11	4635-411	4635-411N
G 4 1/2 - 11	4635-1S11	4635-1S11N
G 5 - 11	4635-511	4635-511N
G 5 1/2 - 11	4635-1W11	4635-1W11N
G 6 - 11	4635-611	4635-611N