

DIAPHRAGM PRESSURE GAUGES

PART NO. 5215-□□□□

STAINLESS STEEL
CASE

STAINLESS STEEL
DIAPHRAGM


STAINLESS STEEL
RING

STAINLESS STEEL
CONNECTION

- Stainless steel case, stainless steel ring, stainless steel connection stainless steel diaphragm
- Used to measure micro pressure and negative pressure of gas that has no corrosion to stainless steel



5215-C1D1W1R15



Part No. example:

5215-C1D1W1R15	C1-connection thread 1/4BSP
	D1-dial size 2.5" DIA
	W1-plastic material window
	R15-pressure range (0~250mbar/0~2500mmHg)

SPECIFICATION

Accuracy class	CL 1.6 for 63mm (2.5"), 100mm (4"); CL 1.0 for 160mm (6.3")
Connection position	bottom
Ambient temperature	-40°C~60°C (-40°F~140°F)
Medium temperature	≤60°C (140°F)

Process connection

C1	1/4BSP (2.5" DIA)
C2	1/4ZG (2.5" DIA)
C3	1/4NPT (2.5" DIA)
C4	3/8BSP (4" DIA, 6.3" DIA)
C5	3/8ZG (4" DIA, 6.3" DIA)
C6	3/8NPT (4" DIA, 6.3" DIA)
C7	1/2BSP (4" DIA, 6.3" DIA)
C8	1/2ZG (4" DIA, 6.3" DIA)
C9	1/2NPT (4" DIA, 6.3" DIA)

Dial size

D1	2.5" DIA
D2	4" DIA
D3	6.3" DIA

Window

W1	tempered glass
W2	safety glass

Pressure range

R1	(-600~0mbar/-6000~0mmHg)
R2	(-400~0mbar/-4000~0mmHg)
R3	(-250~0mbar/-2500~0mmHg)
R4	(-160~0mbar/-1600~0mmHg)
R5	(-100~0mbar/-1000~0mmHg)
R6	(-60~0mbar/-600~0mmHg)
R7	(-40~0mbar/-400~0mmHg)
R8	(-25~0mbar/-250~0mmHg)
R9	(-10~150mbar/-100~1500mmHg)
R10	(0~25mbar/0~250mmHg)
R11	(0~40mbar/0~400mmHg)
R12	(0~60mbar/0~600mmHg)
R13	(0~100mbar/0~1000mmHg)
R14	(0~160mbar/0~1600mmHg)
R15	(0~250mbar/0~2500mmHg)
R16	(0~400mbar/0~4000mmHg)
R17	(0~600mbar/0~6000mmHg)
R18	(0~700mbar/0~7000mmHg)