



MOTORIZED ZOOM MICROSCOPE (BASIC TYPE)

PART NO. 5325-VM100

PROGRAMMABLE SEGMENTED
RING LIGHT

DISPLAY ACTUAL
MAGNIFICATION

- Built-in software without computer
- Can be connected to display and computer at the same time
- Motorized zoom objective
- Display actual magnification
- Programmable segmented ring light
- Take pictures and videos




glass calibration rule
(graduation .004"/0.1mm,
included)



white/black plate
(included)



16G USB flash disk
(included)



360° rotation observation (3D lens is needed)



shortcut keyboard (included)

Shortcut Keyboard Function

- Take picture: take a picture and save it
- Video: record a video
- Freeze: the image can be frozen
- Zoom+: increase the magnification
- Zoom-: reduce the magnification
- Mirror: image horizontal flipover
- Flip: image vertical flipover
- Zoom 1, 2, 3, 4: save the current magnification
- Brightness+: increase the brightness of the light
- Brightness-: reduce the brightness of the light

SPECIFICATION

Sensor	1/2" CMOS
Pixel	2M
Resolution	1920×1080
Magnification	10~68.5X
Measuring accuracy	±.001"
Max workpiece height	9.65"
Frame rate	60fps
Output	USB/LAN/HDMI
Power supply	power adapter
Dimension (L×W×H)	10.28×12.60×18.90"
Weight	11.24lb

MAGNIFICATION, FOCUS DISTANCE AND VIEW FIELD (on 11.6" LCD)

Specification	Objective	
	0.5X (optional)	1X (included)
Magnification	5~34.2X	10~68.5X
Focus distance	7.28"	3.74"
View field	.29×.17~2.09×1.23"	.15×.08~1.04×.61"


STANDARD DELIVERY

Main unit	1 pc
Glass calibration rule	1 pc
Power adapter	1 pc
Mouse	1 pc
16G USB flash disk	1 pc
White/black plate	1 pc
Network cable	1 pc
Shortcut keyboard	1 pc

OPTIONAL ACCESSORY


0.5X auxiliary objective *	5325-VM100-OB05X
3D lens	5325-VM100-3D

* Measurement is not recommended with 0.5X auxiliary objective



can be connected to display and computer at the same time

SOFTWARE FOR LCD (INCLUDED)



SOFTWARE FOR COMPUTER (INCLUDED)

