

# 60° GLOSS METER (BASIC TYPE) PART NO. 5702-DG6

- To test the gloss of coating, such as painting, varnish, printing ink, etc.
- To test the material surfaces, such as metal, granite, ceramic, plastic, paper, etc.
- According to ISO 2813, ISO 7668, ASTM D523, ASTM D2457, DIN 67530
- Automatic judgement after setting high and low limits
- Automatic power off



base with calibration block  
(included)

## SPECIFICATION

|                        |   |
|------------------------|---|
| <b>Incidence angle</b> | 60°   |
| <b>Measuring range</b> | 0~200GU                                     |
| <b>Resolution</b>      | 0.1GU                                       |
| <b>Accuracy</b>        | ±1.5GU (range<120GU)<br>±1.5% (range≥120GU) |
| <b>Repeatability</b>   | 0.2GU (range<120GU)<br>0.2% (range≥120GU)   |
| <b>Zero error</b>      | 0.1GU                                       |
| <b>Measuring area</b>  | .79×.39"                                    |
| <b>Power supply</b>    | rechargeable battery                        |
| <b>Data port</b>       | USB   |
| <b>Dimension</b>       | 5.31×1.77×2.95"                             |
| <b>Weight</b>          | .52lb                                       |

software (included) , test can be controlled from the software, display test data and report

software

measurement data is  
export to EXCEL

report

## STANDARD DELIVERY

|                                    |      |
|------------------------------------|------|
| <b>Main unit</b>                   | 1 pc |
| <b>Base with calibration block</b> | 1 pc |
| <b>U disk</b>                      | 1 pc |
| <b>AC/DC adapter</b>               | 1 pc |
| <b>USB data cable</b>              | 1 pc |
| <b>Cleaning cloth</b>              | 1 pc |