


DATA OUTPUT

- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm, ABS/INC, data hold, TOL, set
- ABS/INC is for absolute and incremental measurement
- TOL is for tolerance measurement
- Battery LR44
- Made of stainless steel
- Data output
- Supplied with bracket to be mounted on the back
- Optional accessory: wireless transmitter (part no. **7315-1150**), data output cable (part no. **7302-SPC7**, keyboard format)

example of application



Part No.	Range	Accuracy	B	C	D	E	F	L
7102-100	4"/100mm	±.0010"	.157"	.787"	.236"	.945"	1.575"	9.646"
7102-150	6"/150mm	±.0015"	.157"	.787"	.236"	.945"	1.575"	11.654"
7102-200	8"/200mm	±.0015"	.157"	.787"	.236"	.945"	1.575"	13.583"
7102-300	12"/300mm	±.0015"	.157"	.787"	.236"	.945"	1.575"	17.520"
7102-400	16"/400mm	±.0020"	.157"	.787"	.236"	.945"	1.575"	21.457"
7102-500	20"/500mm	±.0020"	.217"	.945"	.315"	1.260"	1.772"	26.969"
7102-600	24"/600mm	±.0030"	.217"	.945"	.315"	1.260"	1.772"	30.906"
7102-800	32"/800mm	±.0040"	.217"	.945"	.315"	1.260"	1.772"	38.780"
7102-1000	40"/1000mm	±.0040"	.413"	1.220"	.374"	1.575"	2.362"	49.016"

DIGITAL VERTICAL SCALES



7102-300

