

## **485 DATA OUTPUT CABLES**



7215-50M

- Modbus-RTU protocols
- Can be connected to a PC or PLC
- The baud rate is configurable(9600, 19200, 38400)
- The communication address is configurable

| Part No. | Description                                       | Plug | Connecting with measuring tool                  | Transmit data  |
|----------|---|------|---|--|
| 7215-21  | cable for<br>digital calipers<br>(length 120")    | -1   |   | <ul><li>Acquiring data through host computers</li></ul>      |
| 7215-22  | cable for<br>digital calipers<br>(length 100")    | -111 |   | <ul><li>Acquiring data through<br/>host computers</li></ul>  |
| 7215-30  | cable for digital<br>micrometers<br>(length 100") | -    | for 3102, 3128, 3565 series digital micrometers | <ul><li>Acquisitioning data through host computers</li></ul> |
| 7215-31  | cable for digital<br>micrometers<br>(length 100") |      | 1965<br>13 (500)<br>back                        | <ul><li>Acquiring data through host computers</li></ul>      |

| Part No. | Description                                      | P <b>l</b> ug | Connecting with measuring tool | Transmit data   |
|----------|--|---------------|--------------------------------|---|
| 7215-40M | cable for digital<br>indicators<br>(length 100") |               |                                | <ul><li>Acquiring data through host computers</li></ul> |
| 7215-50M | cable for<br>digital gages<br>(length 100")      |               |                                | <ul><li>Acquiring data through host computers</li></ul> |