## **CONTACT TACHOMETER PART NO. 9224-213**



wheel with 0.1m perimeter (included)



clamping sleeve (included)



cone head

(included)



small cone head (included)

cone cavity head (included)

- Can measure rotary speed, line speed and line length
- Automatically save the maximum value, minimum value and the last value,
  96 data can be stored during continuous measurement
- With backlight display



## **SPECIFICATION**

Measuring range	Rotary speed	0.5~19999RPM	
	Line speed	0.05~500m/min	
	Line length	0.05~99999m	
Resolution	Rotary speed	0.1RPM (range 0.5~999.9RPM) 1RPM (range 1000~19999RPM)	
	Line speed	0.01m/min (range 0.05~99.99m/min) 0.1m/min (range 100~500m/min)	
	Line length	0.02m	
Accuracy Rotary speed		±(0.4%n+1d)RPM (n<300RPM) ±(0.05%n+1d)RPM (n≥300RPM) n is rotary speed, d is resolution	
	Line speed	±(1%+1d)m/min d is resolution	
	Line length	±(1%+1d)m d is resolution	
Sampling time		0.8s (above 60RPM)	
Operating temperature		32~104°F	
Power supply		3×AA batteries	
Dimension		6.7×2.8×1.38"	
Weight		0.36lb	

## STANDARD DELIVERY

0.7.11.27.11.12.22.21.1			
Main unit	1 pc		
Wheel with 0.1m perimeter	1 pc		
Clamping sleeve	1 pc		
Cone head	1 pc		
Small cone head	1 pc		
Cone cavity head	1 pc		
Battery (AA)	3 pcs		