

MINI DIGITAL MULTIMETER (BASIC TYPE)

PART NO. 9242-ML100A

- Portable size with protective case
- 1999 counts digital display
- Data hold
- Display with backlight
- Low battery indication
- Auto power-off
- Safety rating: CAT II 600V



test leads (included)

STANDARD DELIVERY

Main unit	1pc
Battery (AAA)	2pcs
Test lead	2pcs

SPECIFICATION

Function	Range	Resolution	Accuracy ("d" is the least reading)
DC Voltage	200.0mV	.1mV	$\pm(.7\%+3d)$
	2000mV	1mV	$\pm(.5\%+2d)$
	20.00V/200.0V/600V	.01V/.1V/1V	$\pm(.7\%+3d)$
AC Voltage (40~400Hz)	200.0V/600V	.1V/1V	$\pm(1.2\%+3d)$
DC Current	200.0μA/200.0mA	.1μA/.1mA	$\pm(1.0\%+2d)$
	10.00A	.01A	$\pm(1.2\%+5d)$
Resistance	200.0Ω	.1Ω	$\pm(1.0\%+2d)$
	2000Ω/20.00kΩ/200.0kΩ	1Ω/.01kΩ/.1kΩ	$\pm(.8\%+2d)$
	20.00MΩ	.01MΩ	$\pm(1.2\%+3d)$
Battery test	1.5V/9V/12V battery check		
Diode test	open circuit voltage: 2.1V DC		
Continuity test	<50Ω		
Power supply	2×1.5V AAA batteries		
Dimension (L×W×H)	5.28×3.03×1.85"		
Weight	.45lb		