

DC POWER SUPPLY (BASIC TYPE)

PART NO. 9911-PS305-U

- Four-digit LED display
- Output power display
- Output switch control
- Panel locking function to prevent misoperation
- USB interface for power supply
- OVP/OCP protection
- 3 shortcut keys for presetting



test leads (included)

SPECIFICATION

Voltage	Range	30V
	Setting resolution	10mV
	Setting accuracy	$\leq 0.1\% + 20\text{mV}$
	Readback resolution	10mV
	Readback accuracy	$\leq 0.1\% + 20\text{mV}$
	Load regulation	$\leq 0.1\% + 5\text{mV}$
	Line regulation	$\leq 0.01\% + 5\text{mV}$
	Ripple	10mVrms
Current	Range	5A
	Setting resolution	1mA
	Setting accuracy	$\leq 0.2\% + 6\text{mA}$
	Readback resolution	1mA
	Readback accuracy	$\leq 0.2\% + 6\text{mA}$
	Load regulation	$\leq 0.2\% + 3\text{mA}$
	Line regulation	$\leq 0.2\% + 3\text{mA}$
Ripple	8mArms	
OVP	0~33V	
OCP	0~5.5A	
Work condition	temperature: 32°F~104°F, humidity: $\leq 80\%$ RH	
Storage condition	temperature: -4°F~140°F, humidity: $\leq 80\%$ RH	
Cool system	fan cool	
Power supply	AC: 110V $\pm 10\%$, 50Hz/60Hz	
Dimension	9.06x3.15x5.91"	
Weight	3.20lb	

STANDARD DELIVERY

Main unit	1 pc
Test lead	2 pcs