
PORTABLE EDDY CURRENT FLAW DETECTOR Part no. ECT-S610

- Real-time impedance plane and time base sweep display modes available
- Easy to operate menu interface, with universal knob operation is more convenient and fast
- Analyzes the signal waveform of the entire detection process, automatically measuring phase and amplitude.
- With amplitude and phase alarms and settable boundaries
- 5.7" industrial-grade TFT display, can work in outdoor and direct sunlight environment
- 500 sets of data, 500 sets of parameters, or 40 minutes of video
- Applicable to all kinds of metal materials and parts, such as weld cracks, copper pipe, seamless steel pipe, stainless steel pipe, folding, scars, pits, cracks, delamination and other defects, has a high sensitivity










pen probes (included)







SPECIFICATION

SPECIFICATION	
Detection channel	channel1 (X1-Y1)、channel2 (X2-Y2)、mixing channel
Detection frequency	2
Transmission frequency	50Hz~10MHz
Driving voltage	8 adjustable steps
Phase adjustment	360° (1° step)
Gain adjustment	0~90dB (step 0.1dB)
Sampling frequency	40MHz, 12-bit data acquisition
Digital filtering	high pass: 1Hz-1950Hz, low pass: 3Hz-2000Hz
Alarm mode	amplitude and phase alarm
Alarm box	alarm frame modes: off, amplitude phase, half-amplitude phase, square box
Probe Type	bridge
Display	time base, impedance plane
Auxiliary measurements	automatic/manual measurement of amplitude and phase
Balance mode	digital balance
Display modes	dot, line, fade mode
Interface	Q9 interface, USB HOST, Mini HDMI
Environmental temperature	14°F~122°F
Relative humidity	20~95%RH
Power supply	rechargeable lithium battery, working time 6-8 h
Dimensions (L×W×H)	9.88×6.73×2.05"
Weight	3.31lb

STANDARD DELIVERY

Main unit

USB disk

Power adapter

Pen probes 50K~500KHz 1pc Pen probes 500K~3MHz 1pc

1pc

1pc

1pc

Right angle probes 50K~500KHz 1pc

Right angle probes 500K~3MHz 1pc Aluminum alloy flat test block 1pc

Stainless steel plate test block 1pc Hexagon bar wrench 1pc

1pc

Probe connecting cable Mainframe backpack 1pc