

# SELF-LEVELING ROTARY LASER PART NO. GRL-L340

INDICATOR FLASHING  
WHEN OUT OF  $\pm 5^\circ$

IP65  
WATERPROOF

- Applicable fields: construction, decoration, pipeline and equipment installation
- Green laser beam rotates 360° horizontally or vertically
- Self-leveling range  $\pm 5^\circ$  on both X and Y planes
- Alarm when inclination is out of  $\pm 5^\circ$
- $\pm 5^\circ$  leveling range for manual mode on both X and Y planes
- 5 variable speeds 0-600rpm
- 6 scan modes
- Plumb up and plumb down dots
- Remote control for long distance
- Power supply: AC or DC



detector(included)



remote controller(included)



bracket for C battery(included)



beam finder glasses(included)



Tripod(included)

application examples



horizontal leveling

vertical leveling

working with detector

## SPECIFICATION

<b>Working range</b>		indoor 160ft, outdoor 980ft(with detector)
<b>Self leveling range</b>		$\pm 5^\circ$
<b>Horizontal/vertical beam accuracy</b>		$\pm .0001"/1"$
<b>Main laser type</b>		520~540nm, class 2, <1mW
<b>Auxiliary laser type</b>		645~655nm, class 2, <1mW
<b>Rotating speed</b>		0/60/120/300/600rpm
<b>Scanning range</b>		0/10/45/90/180/360°
<b>Setting slope</b>		X axis: $\pm 5^\circ$ , Y axis: $\pm 5^\circ$
<b>Operation temperature</b>		-4~122°F
<b>Maximum remote control distance</b>		65ft
<b>Power supply</b>	<b>Remote controller</b>	2x1.5V AAA batteries
	<b>Main unit</b>	NI-MH batteries or 4x1.5V C batteries
	<b>Detector</b>	1x9V battery
<b>Dimension</b>		8.27x8.27x8.39"
<b>Weight</b>		5.51lb

## STANDARD DELIVERY

<b>Main unit(including NI-MH batteries)</b>	1 pc
<b>C battery and bracket</b>	1 set
<b>Detector</b>	1 pc
<b>Remote controller</b>	1 pc
<b>Beam finder glasses</b>	1 pc
<b>Laser target</b>	1 pc
<b>Power adapter</b>	1 pc
<b>AAA battery</b>	2 pcs
<b>9V battery</b>	1 pc
<b>Tripod</b>	1 pc