

MOTORIZED DIGITAL ROCKWELL/BRINELL/VICKERS HARDNESS TESTER

PART NO. HDT-BRV330-U

INSPECTION
CERTIFICATE


TOUCH
SCREEN

FORCE LOADING BY ELECTRIC
MOTOR (WITHOUT WEIGHTS)

- 5.6" color touch LCD display
- Electronic closed-loop control of the applied test force, easy to use, stable display value
- Total of 21 measurement scales, including Brinell, Rockwell and Vickers test method
- Convertible to various hardness standards such as HB, HV, HRC, HK, etc
- Two types of internal and external illumination are available, and different illumination is used according to the size of the indentation to make the indentation clearer
- Average, maximum and minimum value statistic are available
- Data storage and query function, can be printed out by the printer
- According to ISO 6506, ISO 6507, ISO 6508, ASTM E-10, ASTM E-18, ASTM E-92



Brinell measurement interface



2.36" flat anvil (included)




V-type anvil (included)




5.91" flat anvil (included)

Rockwell measurement interface



Vickers measurement interface



SPECIFICATION

Type	Brinell		Rockwell	Vickers
Test force	306.5N (31.25kg), 612.9N (62.5kg), 1226N (125kg), 1839N (187.5kg)		588N (60kg), 980N (100kg), 1471N (150kg)	49.03N (5kg), 98.07N (10kg), 196.1N (20kg), 294.2N (30kg), 490.3N (50kg), 980.7N (100kg)
Hardness scale	HBW2.5/31.25, HBW2.5/62.5, HBW2.5/187.5, HBW5/62.5, HBW5/125, HBW5/250, HBW10/100, HBW10/250		HRA, HRB, HRC, HRD, HRF, HRG	HV3, HV5, HV10, HV20, HV30, HV50, HV100
Conversion scale	HRA, HRB, HRC, HRD, HRF, HR15N, HR30N, HR45N, HR15T, HR30T, HR45T, HB, HV, HK			
Range	5-650HBW		20-88HRA, 20-100HRB, 20-70HRC	10-2900HV
Stage lifting	manual			
Load control	automatic (load/dwell/unload)			
Eyepiece	10X			
Objective	2.5X (included, for Brinell), 5X (included, for Vickers), 10X (optional , for Vickers)			
Resolution	0.1HB		0.1HR	0.1HV
Load dwell time	0~99 seconds, can be set			
Max. testing width	6.30"			
Max. workpiece height	6.50"		7.09"	6.50"
Power supply	110V, 50/60HZ			
Dimension	21.65×9.25×28.35"			
Weight	176lb			

STANDARD DELIVERY

Main unit	1 pc
Diamond Rockwell indenter	1 pc
Diamond Vickers indenter	1 pc
.098" DIA ball indenter	1 pc
.197" DIA ball indenter	1 pc
1/16" DIA carbide ball indenter	1 pc
5.91" DIA flat anvil	1 pc
2.36" DIA flat anvil	1 pc
V-type anvil	1 pc
Skateboard stage	1 pc
Internal lighting bulb	1 pc
External lighting bulb	1 pc
Hardness test block HRC20~30	1 pc
Hardness test block HRC60~70	1 pc
Hardness test block HRB85~100	1 pc
Hardness test block HBW2.5/187.5	1 pc
Hardness test block HV30	1 pc
Anti-dust cover	1 pc

OPTIONAL ACCESSORY

10X objective	HDT-OB-10
.394" DIA ball indenter	HDT-BRV-INDENTER10
Hardness test block 20~30HRC	HDT-B-HRC1
Hardness test block 35~55HRC	HDT-B-HRC2
Hardness test block 60~70HRC	HDT-B-HRC3
Hardness test block 88~100HRB	HDT-B-HRB
Hardness test block 80~84HRA	HDT-B-HRA
Hardness test block 400~500HBW2.5/187.5	HDT-B-HB25A4
Hardness test block 400~500HV5	HDT-B-HV5D