




DIGITAL SHORE DUROMETERS



- According to ISO868, ISO7619, ASTM D 2240
- Average and peak (max.) mode
- Dwell time is adjustable
- Tolerance testing
- 500 memories
- Wireless connection to printer
- Handhold use or work with test stand (part no. **ISH-DS-STANDA**)
- Automatic power off

SPECIFICATION

Part No.	ISH-DSA	ISH-DSD	ISH-DSOO
Unit	shore A	shore D	shore OO
Test material	soft plastic, soft rubber, etc.	hard plastic, hard rubber, etc.	very soft plastic, rubber, sponge, textile, etc.
Measuring range	0~100HA *	0~100HD *	0~100HOO
Resolution	0.1HA	0.1HD	0.1HOO
Accuracy	±1HA	±1HD	±1HOO
Indenter protrusion	.10"		
Output	wireless and USB		
Power supply	built-in rechargeable battery		
Dimension	6.02×1.97×1.14"		
Weight	.37lb		

* Use **ISH-DSD** when measuring result is higher than 90HA, use **ISH-DSA** when measuring result is lower than 20HD

STANDARD DELIVERY

Main unit	1 pc
Calibration block	1 pc
Software and USB cable	1 pc
AC/DC adapter	1 pc

OPTIONAL ACCESSORY

Printer	ISH-DS-PRINTER
Test stand	ISH-DS-STANDA



software flash disk
(included)



calibration block
(included)



printer (optional)