





LINEAR SCALES (RS422 SIGNAL)



- Connected to digital display box or PLC

ISL-C5-450





| Effective length (L) | Part No. | |
|----------------------|---------------|---------------|
| | Series ISL-C1 | Series ISL-C5 |
| 2"/50mm | ISL-C1-50 | ISL-C5-50 |
| 4"/100mm | ISL-C1-100 | ISL-C5-100 |
| 6"/150mm | ISL-C1-150 | ISL-C5-150 |
| 8"/200mm | ISL-C1-200 | ISL-C5-200 |
| 10"/250mm | ISL-C1-250 | ISL-C5-250 |
| 12"/300mm | ISL-C1-300 | ISL-C5-300 |
| 14"/350mm | ISL-C1-350 | ISL-C5-350 |
| 16"/400mm | ISL-C1-400 | ISL-C5-400 |
| 18"/450mm | ISL-C1-450 | ISL-C5-450 |
| 20"/500mm | ISL-C1-500 | ISL-C5-500 |
| 22"/550mm | ISL-C1-550 | ISL-C5-550 |
| 24"/600mm | ISL-C1-600 | ISL-C5-600 |
| 26"/650mm | ISL-C1-650 | ISL-C5-650 |
| 28"/700mm | ISL-C1-700 | ISL-C5-700 |
| 30"/750mm | ISL-C1-750 | ISL-C5-750 |
| 32"/800mm | ISL-C1-800 | ISL-C5-800 |
| 34"/850mm | ISL-C1-850 | ISL-C5-850 |
| 36"/900mm | ISL-C1-900 | ISL-C5-900 |
| 38"/950mm | ISL-C1-950 | ISL-C5-950 |
| 40"/1000mm | ISL-C1-1000 | ISL-C5-1000 |

| Effective length (L) | Part No. | |
|----------------------|---------------|---------------|
| | Series ISL-C1 | Series ISL-C5 |
| 43"/1100mm | ISL-C1-1100 | ISL-C5-1100 |
| 48"/1200mm | ISL-C1-1200 | ISL-C5-1200 |
| 52"/1300mm | ISL-C1-1300 | ISL-C5-1300 |
| 56"/1400mm | ISL-C1-1400 | ISL-C5-1400 |
| 60"/1500mm | ISL-C1-1500 | ISL-C5-1500 |
| 64"/1600mm | ISL-C1-1600 | ISL-C5-1600 |
| 68"/1700mm | ISL-C1-1700 | ISL-C5-1700 |
| 72"/1800mm | ISL-C1-1800 | ISL-C5-1800 |
| 76"/1900mm | ISL-C1-1900 | ISL-C5-1900 |
| 80"/2000mm | ISL-C1-2000 | ISL-C5-2000 |
| 84"/2100mm | ISL-C1-2100 | ISL-C5-2100 |
| 88"/2200mm | ISL-C1-2200 | ISL-C5-2200 |
| 92"/2300mm | ISL-C1-2300 | ISL-C5-2300 |
| 96"/2400mm | ISL-C1-2400 | ISL-C5-2400 |
| 100"/2500mm | ISL-C1-2500 | ISL-C5-2500 |
| 104"/2600mm | ISL-C1-2600 | ISL-C5-2600 |
| 108"/2700mm | ISL-C1-2700 | ISL-C5-2700 |
| 112"/2800mm | ISL-C1-2800 | ISL-C5-2800 |
| 116"/2900mm | ISL-C1-2900 | ISL-C5-2900 |
| 120"/3000mm | ISL-C1-3000 | ISL-C5-3000 |

SPECIFICATION

| Part No. | Series ISL-C1 | Series ISL-C5 |
|-----------------------------|--|----------------------------------|
| L1 (inch) | L+1.18" (L<38"), L+1.97" (L≥38") | L+1.18" (L<38"), L+1.97" (L≥38") |
| L2 (inch) | L+5.35" (L<38"), L+5.35" (L≥38") | L+5.35" (L<38"), L+5.35" (L≥38") |
| L3 (inch) | L+6.06" (L<38"), L+6.85" (L≥38") | L+6.06" (L<37"), L+6.85" (L≥37") |
| Resolution | .00005" | .0002" |
| Thickness | 1.14" | |
| Max. response speed | 196ft/min | |
| Scale grating pitch | 787μin | |
| Scale reference point pitch | 1.97" | |
| Accuracy | ±(197+5L)μin, L is the effective length in inch | |
| Cable length | 140" (L: 2-38"), 200" (L: 40-76"), 400" (L: 80-120") | |
| Output signal | RS422 | |
| Socket | 9PD | |
| Power supply | 5±0.25V | |

STANDARD DELIVERY

| | |
|----------------------|------------------|
| Main unit | 1 pc |
| 'L' shape support | 1 pc |
| Anti-dust cover | 1 pc |
| Plain base | 1 pc (for L≥60") |
| Mounting accessories | 1 package |