

TOOL PRESETTER PART NO. ISP-A350

INSIZE PLUS
MADE IN EUROPE

CHECK, PRESET AND MEASURE
CUTTING TOOLS

AUTOMATIC RECOGNITION
OF CUTTING EDGE SHAPES

DATA OUTPUT

air flotation button, rapid
movement of X and Z axis



CCD camera and
LED surface light source



LED contour
light source



vacuum
clamping
(optional) 360°
clamping
(included) 4x90°
clamping
(included)

key function



ISO/SK/BT50 spindle (included)

7" DFT color display




image display

result

operation button

controller (included)

printer (included)

- Check, preset and measure cutting tools
- Telecentric lens CCD camera system
- Use Bosch or Festo pneumatic components, THK guideways and HEIDENHAIN scales
- Built-in 104 cutting edge shapes, automatic recognition
- Measuring modes: absolute, relative and incremental measurement
- Measuring radius, angle, concentricity, axial runout, etc
- Storage of 1000 tool parameters
- View, print and export measurement results




attach the printed label on the tool




ISO/SK/BT50 to HSK63
A/C/E, HSK80 B/D/F
converter **(optional)**




ISO/SK/BT50 to ISO/SK/BT40
converter **(optional)**



automatic recognition of cutting edge shapes



can store 99 sets of converter parameters and automatically prompt to check the zero position at fixed time



scan and measure the maximum profile of the cutting tool



check cutting edge wear

SPECIFICATION

Maximum tool diameter (X axis)	12.60"	
Maximum tool height (Z axis)	13.75"	
Repeatability	X axis	.00008"
	Z axis	.00008"
X/Z axis resolution	.00004"	
Camera	color CCD	
Image processing accuracy	.00004"	
Magnification	12X	
View field	.28x.28"	
Illumination	adjustable LED light	
Spindle	ISO/SK/BT50 (concentricity .00008")	
Date output	USB, RS232	
Working air pressure	87~116psi (0.6~0.8MPa)	
Environmental requirement	temperature: 41~95°F	
	relative humidity: 10%~95%	
Power supply	100~240V, 50/60Hz	
Dimension (L×W×H)	47.24×15.75×34.25"	
Weight	176lb	

STANDARD DELIVERY

Main unit	1 pc
Controller	1 pc
ISO/SK/BT50 spindle (including 360° clamping and 4×90° clamping)	1 pc
Printer	1 pc
Printer label paper	1 pc

OPTIONAL ACCESSORY

ISO/SK/BT50 to ISO/SK/BT40 converter	ISP-A350-C1
ISO/SK/BT50 to ISO/SK/BT30 converter	ISP-A350-C5
ISO/SK/BT50 to HSK63 A/C/E, HSK80 B/D/F converter	ISP-A350-C2
ISO/SK/BT50 to HSK50 A/C/E, HSK63 B/D/F converter	ISP-A350-C3
ISO/SK/BT50 to HSK40 A/C/E, HSK50 B/D/F converter	ISP-A350-C4
ISO/SK/BT50 to HSK32 A/C/E, HSK40 B/D/F converter	ISP-A350-C6
Spindle vacuum clamping	ISP-A350-VC
Printer label paper	ISP-A350-TAB