

# HORIZONTAL PROFILE PROJECTORS



ISP-W3020-U



ISP-A3000E-U



digital readout of ISP-A3000E-U

- touch buttons
- USB data output to Excel
- show diagram



software flash disk (included, only for ISP-A3000E-U)

## OPTIONAL ACCESSORY



lens



1.97"/50mm reading scale (check magnification accuracy)




demo sample



vise



rotary table



11.81" DIA/Ø300mm overlay chart (protractor with 1° graduation, radius with .039"/1mm increment)



11.81"/300mm calibration scale (check magnification accuracy together with 1.97"/50mm reading scale or calibrate measuring accuracy)



printer (only for ISP-A3000E-U)

**SPECIFICATION**

Part No.		ISP-W3020-U		ISP-A3000E-U		
Edge detector		not included		included		
Lens	magnification	10X (included)	20X (optional)	50X (optional)	100X (optional)	
	view field	1.18" DIA	.59" DIA	.24" DIA	.12" DIA	
	working distance	3.06"	1.74"	1.51"	1.00"	
Magnification accuracy		±0.08%				
Projector screen		diameter: 12" DIA				
		rotation range: 0°~360°, resolution: 1" or 0.01°				
		reference lines: cross-hairs				
Stage	metal stage size	15.75"×5.91"				
	turning range	±15°				
	X-Z stage travel	range: 8"×4"				
		resolution .00002"				
	Y (focus) travel range	accuracy: (157.5+40L)μin L is the measuring length in inch				
max. load capacity	2.95"					
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable				
		surface illumination: 24V/150W halogen lamp (with 2 fibers), position is adjustable				
Data processing unit	display	X-Z stage travel, screen rotation				
	output	RS232C		RS232C, USB (data output to Excel)		
	function		measure coordinate of point		measure coordinate of point	
			measure coordinate of line		measure coordinate of line	
			measure center coordinate, radius of circle with three points		measure center coordinate, radius of circle with three points	
		measure distance between two objects		measure distance between two objects		
		measure angle with four points or two lines		measure angle with four points or two lines		
		set origin of coordinate		coordinate transform		
		coordinate transform		choose measurement object automatically according to the selective point and display the result		
advanced function	—		programming for batch measurements			
Power supply		110 V, 50/60Hz				
Dimension (L×W×H)		32.68×42.91×39.76"				
Net weight		352lb				

**STANDARD DELIVERY**

Main unit	1 pc
10X lens	1 pc
Overlay chart clip	4 pcs
Foot-switch	1 pc
Anti-dust cover	1 pc
Software (only for ISP-A3000E-U) and USB cable	1 pc

**OPTIONAL ACCESSORY**

20X lens	ISP-A3000-LENS20X
50X lens	ISP-A3000-LENS50X
100X lens	ISP-A3000-LENS100X
Overlay chart	ISP-A1000-CHART
50mm reading scale	ISP-A1000-SCALE50
300mm calibration scale	ISP-A1000-RULE

Swivel center support	ISP-A3000-SUPPORT
Demo sample	ISP-A1000-DEMO
V-block with clamp	ISP-A3000-VBLOCK
Rotary table	ISP-A3000-RTABLE
Vise	ISP-A3000-VISE
Printer (only for ISP-A3000E-U)	ISP-A1000-PRINTER