

HORIZONTAL PROFILE PROJECTORS



ISP-W4025-U



ISP-A7000E-U

digital readout of ISP-A7000E-U

- touch buttons
- USB data output to Excel
- show diagram






software flash disk (included, only for ISP-A7000E-U)

OPTIONAL ACCESSORY



lens



vise



rotary table



demo sample (need rotary table)



printer (only for ISP-A7000E-U)



1.97"/50mm reading scale (check magnification accuracy)



11.81"/300mm calibration scale (check magnification accuracy together with 1.97"/50mm reading scale or calibrate measuring accuracy)

SPECIFICATION

Part No.		ISP-W4025-U			ISP-A7000E-U		
Edge detector		not included			included		
Lens	magnification	5X (optional)	10X (standard)	20X (optional)	50X (optional)	100X (optional)	
	view field	3.15" DIA	1.57" DIA	.79" DIA	.31" DIA	.16" DIA	
	working distance	3.69"	4.09"	3.74"	2.59"	1.38"	
Magnification accuracy		±0.08%					
Image		erect image					
Projector screen		diameter: 16" DIA					
		rotation range: 0°~360°, resolution: 1" or 0.01"					
		reference lines: cross-hairs					
Stage	metal stage size	17.72×7.87"					
	turning range	±15°					
	X-Z stage travel	range: 10×6"					
		resolution .00002"					
	Y (focus) travel range	accuracy: (157.5+40L)µin L is the measuring length in inch					
max. load capacity	110.23lb						
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable					
		surface illumination: 21V/150W halogen lamp (with 2 fibers), position is adjustable					
Data processing unit	display	X-Z stage travel, screen rotation					
	output	RS232C			RS232C, USB (data output to Excel)		
	function		measure coordinate of point				measure coordinate of point
			measure coordinate of line				measure coordinate of line
		measure center coordinate, radius of circle with three points				measure center coordinate, radius of circle with three points	
		measure distance between two objects				measure distance between two objects	
		measure angle with four points or two lines				measure angle with four points or two lines	
		set origin of coordinate				coordinate transform	
		coordinate transform				choose measurement object automatically according to the selective point and display the result	
		set midpoint of coordinate					
advanced function	—			programming for batch measurements			
Power supply		110 V, 50/60Hz					
Dimension (L×W×H)		25.43×47.83×47.64"					
Net weight		529lb					

STANDARD DELIVERY

Main unit	1 pc
10X lens	1 pc
Overlay chart clip	4 pcs
Foot-switch	1 pc
Anti-dust cover	1 pc
Software (only for ISP-A7000E-U) and USB cable	1 pc

OPTIONAL ACCESSORY

5X lens	ISP-A7000-LENS5X
20X lens	ISP-A7000-LENS20X
50X lens	ISP-A7000-LENS50X
100X lens	ISP-A7000-LENS100X
300mm calibration scale	ISP-A1000-RULE
50mm reading scale	ISP-A1000-SCALE50

Swivel center support (for ISP-A7000E-U/ISP-W4025-U)	ISP-A3000-SUPPORT
Demo sample	ISP-A1000-DEMO
V-block with clamp	ISP-A3000-VBLOCK
Rotary table	ISP-A3000-RTABLE
Vise	ISP-A3000-VISE
Printer (only for ISP-A7000E-U)	ISP-A1000-PRINTER