

IMPACT SPECIMEN NOTCH PROJECTORS

- Suitable for inspecting the notching quality of impact specimens of Charpy V-notch (depth of 2mm) and U-notch (depth of 2mm)
- Standard sample drawings with tolerances, angle values and depth lines on the screen for intuitive and efficient comparison

SPECIFICATION

Part No.	ISP-Z1-U	ISP-Z2-U
Corresponding standard	GB/T 229	GB/T 229, ASTM E23, ISO 148, ISO 83, EN 10045
Magnification	50X	
Magnification of lens	2.5X	
Magnification of projector lens	20X	
Diameter of projector screen	Ø200mm	
Size of square stage	110×125mm	
Size of round stage	Ø90mm	
Diameter of glass on stage	Ø70mm	
Stroke of stage (X axis)	±10mm	
Stroke of stage (Y axis)	±10mm	
Stroke of stage (Z axis)	±12mm	
Range of stage rotation	0°~360°	
Illumination (tungsten halogen lamp)	12V 100W	
Power supply	AC 110V, 60Hz 150W	
Dimension (W×D×H)	20.08×8.66×23.62"	
Weight	44.09lb	

CAN BE
CUSTOMIZED



ISP-Z1-U

STANDARD DELIVERY

Main unit	1 pc
-----------	------