

ATTENTION: NOT SUITABLE FOR HIGH SPEED SHOCK TORQUE MEASUREMENT



## **DIGITAL TORQUE TESTERS**










IST-04TT815 type B

- Test torque wrenches, torque screwdrivers and other torque tools
- Clockwise operation
- Peak, track and first peak working modes
- Tolerance testing
- LED indicator for target torque alarm:
  - Green LED light on when the value is within tolerance;
  - Red LED light on when the value is above the high tolerance
- Ability to upload data in real time, save data and export data to EXCEL
- Power off automatically in 2 minutes without any operations
- Supplied with manufacturer inspection certificate



software (included)



adaptor (type A included)

## STANDARD DELIVERY

Main unit	1 pc			
Transmission cable and software	1 pc			
AC/DC adapter	1 pc			
Adaptor	refer to details			

## **SPECIFICATION**

SELCIFICATION								
Part No.	IST-04TT5	IST-04TT28	IST-04TT68	IST-04TT350	IST-04TT815	IST-04TT1000	IST-04TT2000	
Туре	A				В			
Range	4.42~44.2in.lb	24.8~247.8in.lb	60.2~602in.lb	310~3097in.lb	_	<b>—</b>	_	
	.369~3.69ft.lb	2.06~20.65ft.lb	5.01~50.1ft.lb	25.8~258.1ft.lb	60.1~601ft.lb	74~738ft.lb	148~1475ft.lb	
Accuracy	±1% (clockwise)							
Resolution	.01in.lb	.1in.lb	.1in.lb	1in.lb	_	_	_	
	.001ft.lb	.01ft.lb	.01ft.lb	.1ft.lb	.1ft.lb	1ft.lb	1ft.lb	
Unit	in.lb, ft.lb, kg.cm, N.m				N.m, ft.lb			
Square socket /hex driver	1/4"	3/8"	3/8"	1/2"	1.06"	1.06"	1.06"	
Power supply	AC 100~240V, 50/60Hz							
Weight	1.65lb	1.65lb	2.43lb	2.43lb	11.24lb	11.24lb	11.24lb	
						· ·		