

# DIGITAL TORQUE TESTERS

ATTENTION: NOT SUITABLE FOR ELECTRIC WRENCHES, IMPACT WRENCHES OR PNEUMATIC WRENCHES



**IST-04TT350**  
type A



**IST-04TT815**  
type B

- Test torque wrenches, torque screwdrivers and other torque tools
- Clockwise operation
- Peak, track and first peak working modes
- Tolerance testing
- LED indicator for the target torque alarm:  
green LED light on when the value is within tolerance; red LED light on when the value is above the high tolerance
- Power off automatically in 2 minutes without any operations

## SPECIFICATION

Part No.	IST-04TT5	IST-04TT28	IST-04TT68	IST-04TT350	IST-04TT815	IST-04TT1000	IST-04TT2000
Type	A				B		
Range	4.42~44.2in.lb 0.369~3.69ft.lb	24.8~247.8in.lb 2.06~20.65ft.lb	60.2~602in.lb 5.01~50.1ft.lb	310~3097in.lb 25.8~258.1ft.lb	— 60.1~601ft.lb	— 74~738ft.lb	— 148~1475ft.lb
Accuracy	±1% (clockwise)						
Resolution	0.01in.lb 0.001ft.lb	0.1in.lb 0.01ft.lb	0.1in.lb 0.01ft.lb	1in.lb 0.1ft.lb	— 0.1ft.lb	— 1ft.lb	— 1ft.lb
Unit	in.lb, ft.lb, kg.cm, N.m					N.m, ft.lb	
Square socket/hex driver	1/4"	3/8"	3/8"	1/2"	1.06"	1.06"	1.06"
Power supply	DC						
Weight	1.65lb	1.65lb	2.43lb	2.43lb	11.24lb	11.24lb	11.24lb

## STANDARD DELIVERY

Main unit	1 pc
AC/DC adapter	1 pc