

BLUETOOTH DIGITAL TORQUE WRENCHES (KEYBOARD SIGNAL)

TYPE B OPTIONAL ACCURACY:
CLOCKWISE: ±1%
COUNTER-CLOCKWISE: ±2%



BUILT-IN BLUETOOTH



IST-15W12A
type A



IST-15W135A
type B

Torque wrenches:

- Unit: in.lb, ft.lb, N.m, kg.cm
- Clockwise and counter-clockwise operation
- Peak and track working mode
- Can set tolerance with judgement in peak working mode
- 9 target torque values can be set, with audible and visible alarm:
LED lights up in sequence, and the buzzer gets louder and louder when torque value is 80%~99.5% of target torque
- Power off in 2 minutes automatically
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)

Data transmission:

- Built-in Bluetooth 4.0 module, which can be connected with computers (with Bluetooth function), mobile phones, tablets and other devices
- Keyboard signal, can be transmitted to Excel, Word, TXT
- Transmission distance is 32.81 feet (no obstacles, no electromagnetic interference)
- Bluetooth connection and disconnection are respectively shown by indicator lights



transmission distance is 32.81 feet
(no obstacles, no electromagnetic interference)

SPECIFICATION

| Part No. | IST-15W06A | IST-15W12A | IST-15W20A | IST-15W30A | IST-15W135A | IST-15W200A | IST-15W340A |
|-------------------------|---------------------------------|-----------------|-----------------|-----------------|---------------|---------------|---------------|
| Type | A (short handle) | | | B (long handle) | | | |
| Range | 10.6~53.09in.lb | 21.2~106.2in.lb | 35.4~177.0in.lb | 53.1~265.5in.lb | 239~1195in.lb | 354~1770in.lb | 602~3009in.lb |
| Accuracy | clockwise | ±2% | | | | | |
| | counter-clockwise | ±3% | | | | | |
| Tolerance setting range | -20%~+20% (target torque value) | | | | | | |
| Resolution | 0.01in.lb | 0.1in.lb | 0.1in.lb | 0.1in.lb | 1in.lb | 1in.lb | 1in.lb |
| Square driver (L) | 1/4" | 1/4" | 1/4" | 1/4" | 3/8" | 1/2" | 1/2" |
| Power supply | 2xAAA batteries | | | 2xAA batteries | | | |
| Length | 8.46" | 8.46" | 8.46" | 15.35" | 16.34" | 20.87" | 25.59" |
| Weight | 1.65lb | 1.65lb | | 1.68lb | 2.07lb | | 3.40lb |

OPTIONAL ACCESSORY

| | |
|-------------------|--------------|
| Calibration cable | IST-SD-CABLE |
|-------------------|--------------|