

INSPECTION CERTIFICATE

- Unit: N.m, in.lb, ft.lb, kg.cm
- Clockwise and count-clockwise operation
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
 - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)

SWING-HEAD DIGITAL TORQUE WRENCHES



SPECIFICATION

SFECIFICATION				
Part No.	IST-21W30A	IST-21W135A	IST-21W200A	IST-21W340A
Range	53.0~265.5in. l b	239~1195in. l b	354~1770in. l b	602~3009in. l b
	6~30N.m	27~135N.m	40~200N.m	68~340N.m
Accuracy	clockwise: ±2% (when ratchet head is flush with grip)			
	counter-clock wise: ±3% (when ratchet head is flush with grip)			
Resolution	.1in. l b	1in. l b	1in .l b	1in .l b
	0.01N.m	0.1N.m	0.1N.m	0.1N.m
Square driver (L)	1/4"	3/8"	1/2"	1/2"
Power supply	2×AA batteries			
Length	15.35"	16.34"	20.87"	25.59"
Weight	1.67 l b	2.07 l b	2.95 l b	3.39 l b



swing-head ratchet head

OPTIONAL ACCESSORY

Calibration cable IST-W-CABLE