

ADJUSTABLE OPEN HEAD DIGITAL TORQUE WRENCHES



**ATTENTION: CLOCKWISE
OPERATION ONLY**

- The movable jaw of the adjustable open head has a protruding positioning design to ensure accuracy
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
 - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)



IST-24W135A26

OPTIONAL ACCESSORY

Calibration cable

IST-W-CABLE

SPECIFICATION

Code	IST-24W60A26	IST-24W85A26	IST-24W135A26	IST-24W135A30	IST-24W200A30	IST-24W200A41	IST-24W340A41
Range	106.2~531in.lb	150.4~752in.lb	239~1195in.lb	239~1195in.lb	354~1770in.lb	354~1770in.lb	602~ 3009in.lb
	8.84~44.24ft.lb	12.54~62.7ft.lb	19.9~99.5ft.lb	19.9~99.5ft.lb	29.5~147.5ft.lb	29.5~147.5ft.lb	50.1~250.7ft.lb
Adjustable open range	.197~1.02"	.197~1.02"	.197~1.02"	.197~1.18"	.197~1.18"	.394~1.61"	.394~1.61"
Accuracy	clockwise: $\pm 3\%$						
Resolution	0.1in.lb	1in.lb	1in.lb	1in.lb	1in.lb	1in.lb	1in.lb
	0.01ft.lb	0.1ft.lb	0.1ft.lb	0.1ft.lb	0.1ft.lb	0.1ft.lb	0.1ft.lb
Power supply	2×AA batteries						
Length	16.85"	16.85"	16.85"	20.67"	20.67"	25.59"	25.59"
Weight	2.62lb	2.62lb	2.62lb	3.08lb	3.08lb	3.53lb	3.53lb