

DIGITAL TORQUE WRENCHES



OPTIONAL ACCURACY:
 CLOCKWISE: ±1%
 COUNTER-CLOCKWISE: ±2%
 ONLY FOR RANGE 53.1~7521in.lb



- Clockwise and counter-clockwise operation
- Unit: in.lb, ft.lb, N.m, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
 - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)

SPECIFICATION

Part No.	Type	Range		Accuracy	Resolution		Square driver (L)	Power supply	Length	Weight
IST-W30A	A	53.1~265.5in.lb	4.42~22.12ft.lb	clockwise: ±2% counter-clockwise: ±3%	0.1in.lb	0.01ft.lb	1/4"	2×AA batteries	15.35"	1.83lb
IST-W135A		239~1195in.lb	19.9~99.5ft.lb		1in.lb	0.1ft.lb	3/8"		16.34"	2.09lb
IST-W200A		354~1770in.lb	29.5~147.5ft.lb		1in.lb	0.1ft.lb	1/2"		20.87"	3.09lb
IST-W340A		602~3009in.lb	50.1~250.7ft.lb		1in.lb	0.1ft.lb	1/2"		25.59"	3.53lb
IST-W500A*	B	885~4424in.lb	73.7~368.7ft.lb	clockwise: ±2.5% counter-clockwise: ±3.5%	1in.lb	0.1ft.lb	3/4"		50.59"	15.43lb
IST-W850A		1504~7521in.lb	125.4~626.8ft.lb		1in.lb	0.1ft.lb	3/4"		50.98"	13.23lb
IST-W1200A		—	177~885ft.lb		—	1ft.lb	1"		75.59"	28.66lb
IST-W1500A		—	221~1106ft.lb		—	1ft.lb	1"		75.59"	28.66lb
IST-W2000A		—	295~1476ft.lb		—	1ft.lb	1"	75.59"	30.86lb	

OPTIONAL ACCESSORY

Calibration cable	IST-W-CABLE
-------------------	-------------

* The accuracy of this part No. is not optional