

SHORT HANDLE DIGITAL TORQUE WRENCHES



- Clockwise and counter-clockwise operation
- Unit: in.lb, ft.lb, N.m, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
 - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off in 5 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)



IST-WS60

SPECIFICATION

Part No.	IST-WS12	IST-WS20	IST-WS30	IST-WS30A	IST-WS60	IST-WS85
Range	21.2~106.2in.lb	35.4~177.0in.lb	53.1~265.5in.lb	53.1~265.5in.lb	106.2~530.9in.lb	150~752in.lb
	1.77~8.85ft.lb	2.95~14.75ft.lb	4.42~22.12ft.lb	4.42~22.12ft.lb	8.85~44.24ft.lb	12.5~62.7ft.lb
Accuracy	clockwise ±3%					
	counter-clockwise ±4%					
Resolution	0.1in.lb	0.1in.lb	0.1in.lb	0.1in.lb	0.1in.lb	1in.lb
	0.01ft.lb	0.01ft.lb	0.01ft.lb	0.01ft.lb	0.01ft.lb	0.1ft.lb
Square driver (L)	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"
Power supply	2×AAA battery					
Length	8.46"	8.46"	8.46"	8.46"	8.86"	10.67"
Weight	1.65lb	1.65lb	1.65lb	1.83lb	2.02lb	2.21lb

OPTIONAL ACCESSORY

Calibration cable	IST-SD-CABLE
-------------------	--------------