

VIDEOSCOPES (BASIC TYPE)














SPECIFICATION

Part No.		ISV-J2810	ISV-J2815	ISV-J4010	ISV-J4030	ISV-J6010	ISV-J6030
Lens	diameter (D)	.110" DIA	.110" DIA	.157" D I A	.157" DIA	.236" DIA	.236" DIA
	pixel	0.16M		1M			
	resolution	400×400		1280×720			
	depth of field	.394~∞"	.394~∞"	.394~∞"	.394~∞"	.394~∞"	.394~∞"
	bending direction	four directions	four directions	four directions	four directions	four directions	four directions
	bending range (α)	±160°					
	angle of view (θ)	120°					
	illumination	front LED					
	lens	sapphire glass lens					
	dust/waterproof	IP67					
	bend control	manual joystick					
Cable	length	40"	60"	40"	120"	40"	120"
	type	wire weaved cable					
Main unit	display	5" HD screen (resolution: 1920×1080)					
	function	take pictures, take videos					
	file format	picture: JPG, video: MOV					
	image process	image zoom (1X, 2X, 3X, 4X, 5X)					
	image control	freeze, flip over, playback, analog ruler					
	memory	32G memory card					
	output	WIFI (only for Android OS), USB, HDMI					
	power supply	rechargeable lithium battery (working time ≥ 4 hours), AC/DC adapter (for continuous working)					
Weight		2.205 l b					

STANDARD DELIEVERY OPERATION ENVIRONMENT Main unit Main unit 14~122°F, no preheat 1 pc 32G SD card Operation temperature -4~158°F 1 pc Card reader 1 pc Storage temperature -4~140°F USB cable 1 pc Relative humidity maximum 90%, no condensation

AC/DC adapter

1 pc