

MOUNTING PRESSES (ADVANCED TYPE)



MLP-MP43-U



MLP-MP53-U

- Built-in heating and cooling structure reduces the mounting time to 6 minutes
- The programmed control system reserves 10 customized preparation schemes to meet different mounting requirements
- The thickness of the middle mold is up to 15mm, and 2 samples can be mounted at the same time at one station
- Can accurately control the pressure size, adjustment range: 1~20MPa



hot mounting resin(included)

SPECIFICATION

Code	MLP-MP43-U	MLP-MP53-U
Station number	1	2
Power	1100W+Heating power *	1200W+Heating power*2
Mounting diameter	1.18" DIA (Customizable .98" DIA, 1.57" DIA, 1.97" DIA)	
System pressure	1~20MPa, Optional increase or decrease 1MPa	
Pressure mode	Automatic electro-hydraulic	
Cooling mode	Automatic water cooling **	
Heating range	194~392°F	
Holding time	0~10min	
Cooling temperature/time	104~194°F/0~10min	
Power supply	AC 110V, 60Hz	
Weight	88.18lb	169.76lb
Dimension	20.87×19.09×18.23"	26.42×19.09×18.23"

* Heating power of mounting sleeve: 1800W (mounting diameter≤1.25"), 2400W (mounting diameter ≥1.5")

** Cooling water pressure should not be higher than 1MPa, must be filtered through 1.57μin (40μm) filter

STANDARD DELIVERY

Main unit	1pc
Hot mounting resin	1bottle (.55lb)
Funnel	1pc
Filter	1pc
vacuum cleaner tip	1pc

OPTIONAL ACCESSORY

Description	Code	Specification
Hot mounting resin	MLP-DR3	black, 8.82lb