

## RECHARGEABLE UV FLAW DETECTION LIGHT PART NO. MPI-HF360

- UV-B content is 0
- Without preheating, instant start, instant on/off, no need to wait
- Supplied with glass filter
- External surface temperature increase <8K (46.4°F) for continuous working



goggles (included)



### SPECIFICATION

|                          |   |
|--------------------------|---|
| UV (Light) Lux           | about 6000 $\mu$ W/cm <sup>2</sup>                                |
| UV light power           | UV LED-12VA   |
| Covering area            | diameter approximately 11.81" DAI (calibrated at 15.00" distance) |
| FLUX error               | $\pm$ 10% (at 32°F~104°F)   |
| White light content      | $\leq$ 20LUX  |
| Lighting characteristics | centerlighting  |
| Wavelength               | 365nm $\pm$ 3nm (UVA), at temperature 77°F                        |
| Power supply             | 10.8V rechargeable lithium battery                                |
| Battery capacity         | 3200mAh   |
| Charging time            | 3h~4h   |
| Battery life             | UV LED 5h~6h  |
| Dimension                | 6.89 $\times$ 2.95 $\times$ 6.69"                                 |
| Weight                   | 1.65lb  |

### STANDARD DELIVERY

|           |      |
|-----------|------|
| Main unit | 1pc  |
| Battery   | 2pcs |
| Charger   | 1pc  |
| Goggles   | 1pc  |