

INDUSTRIAL AUTOMATIC X-RAY FILM PROCESSOR

PART No. RXT-P820-U

- Microcomputer infrared control system, capable of automatic/manual replenishment of processing chemicals, automatic constant temperature
- Built-in red indicator light, magnetically adjustable dimming, check the film feeding status
- Double sink to ensure clear image
- Adjustable roller arrangement structure ensures no indentation
- Designed with timed start function to prevent crystallization
- Independent bridge design with tail fins to prevent chemical splashing
- Developing, fixing, washing, independent circulation system
- The drying and heating system is adjustable in high and low levels
- Professional cone-shaped air duct system ensures even film drying and prevents watermarks formation



pre-filter (optional)

SPECIFICATION

Film sizes	3.15"×3.94" to 16.93"×∞"
Process time	6~14min (adjustable in 1 minute intervals)
Processing capacity	18~42sheets/h (14.02"×17.01"), 88~260sheets/h (3.15"×14.17")
Developer time	100~210s
Developer tank capacity	3.43gal
Fixer tank capacity	3.43gal
Water tank capacity	3.96gal
Replenishment	.01~.13gal/m ²
Developer temperature	68~104°F (adjustable)
Fixer temperature	68~104°F (adjustable)
Drying temperature	68~158°F (adjustable)
Water temperature	41~86°F
Water consumption	.528gal/min
Power supply	100~110V, 50Hz/60Hz
Dimension (L×W×H)	41.34"×28.35"×48.42"
Net weight	209.44lb

STANDARD DELIVERY

Main unit	1 pc
Water inlet pipe	1 pc
Drain pipe (with valve)	3 pcs
Replenishment pipe (with nozzle)	2 pcs
Overflow pipe	3 pcs
Liquid medicine barrel (6.60gal)	2 pcs
Spare parts kit	1 pc

OPTIONAL ACCESSORY

Pre-filter	RXT-PC01
------------	----------