

AUTOMATIC SPRING TESTING MACHINES

- Applicable to all kinds of springs for tension and compression tests
- Preloading function, can set the times of preload, residual height, deformation, force value
- Automatic merging function
- Automatic continuous test, test method can be set up
- With specimen fracture stop, force value overload protection, beam limit position protection
- With overload, overcurrent, leakage protection functions



computer and solfware (included)



SRT-W20-U



extension spring test



compression spring test



slender spring test



arbor fixture (optional)

SPECIFICATION

SPECIFICATION							
Part No.	SRT-W1-U	SRT-W2-U	SRT-W5-U	SRT-W10-U	SRT-W20-U	SRT-W50-U	SRT-W100-U
Max. test force	1N	2N	5N	10N	20N	50N	100N
Resolution of test force	0.001N	0.001N	0.001N	0.001N	0.001N	0.003N	0.01N
Accuracy class	0.5 class						
Accuracy of test force	±0.5% of indicating value						
Range of displacement speed	0.01~300mm/min						
Resolution of displacement	0.001mm						
Accuracy of displacement	±(50+0.15L)µm (Note: L is the distance between the compression fixtures, mm)						
Test travel	100mm						
Power supply	AC 110V, 60Hz						
Dimension	7.87×11.02×20.08"						
Weight	44.09lb						

STANDARD DELIVERY

0171112711127111111				
Main unit	1 pc			
Computer	1 pc			
Software	1 set			
Printer	1 pc			
Pull clamp	1 set			
Compression fixture	1 set			

OPTIONAL ACCESSORY

0. How. 2.002000101				
Arbor fixture	customized, selection of specifications			
Fixture	according to test requirements			