

## ELECTRIC THERMOSTATIC WATER BATHS

- Suitable for biomedical industry, chemical industry, education and scientific research, etc.
- Stainless steel inner tank, rounded corner design, multiple test port cover dimensions available
- Intelligent temperature controller, provides precise and reliable temperature control, features PID auto-tuning function
- Equipped with over-temperature alarm function to ensure samples safety



WTB-A101-U

### SPECIFICATION

Part No.	WTB-A101-U	WTB-A102-U	WTB-A103-U	WTB-A104-U
Temperature range	RT+10°C~100°C			
Temperature resolution	0.1°C			
Temperature deviation	±1°C			
Temperature fluctuation	±0.5°C			
Temperature uniformity	≤1°C			
Test port	2pcs	4pcs	6pcs	8pcs
Test port cover dimension	Ø1.77", Ø2.56", Ø3.35", Ø4.13", Ø4.92"			
Material	shell: cold-rolled steel plate with powder coating; inner tank, cover plate, partition plate: stainless steel plate			
Power supply	AC110V, 60Hz			
Power	500W	800W	1500W	2000W
Working area dimension (L×W×H)	9.45×5.51×4.33"	11.81×9.45×4.33"	19.69×11.81×5.91"	21.65×13.78×5.91"
External dimension (L×W×H)	14.17×7.48×8.07"	16.54×11.42×8.07"	25.79×13.78×8.07"	28.54×16.54×8.27"
Weight	8.82lb	13.23lb	19.84lb	24.25lb

### STANDARD DELIVERY

Main unit	1 pc
Partition plate	1 pc
Cover plate	1 pc
Test port cover	1 set